


MATERIAL SAFETY DATA SHEET

| | | | | | |
|---|----------------------------|---------------------|---------------------------|--|--------------|
| OSHA - Meets 29 CFR 1910.1200 Standards | | HMIS HAZARD RATINGS | | | |
|  | HEALTH | 0 | * = Chronic Health Hazard | | 2 = MODERATE |
| | FLAMMABILITY | 0 | 0 = INSIGNIFICANT | | 3 = HIGH |
| | PHYSICAL HAZARD | 0 | 1 = SLIGHT | | 4 = EXTREME |
| | TRANSPORTATION INFORMATION | | | | |
| | PROPER SHIPPING NAME: | | Wipe On Paint protectant | | |
| HAZARD CLASS / PKG GRP: | | C | | | |

| | | |
|--|--|-------------|
| IDENTITY | | Page 1 of 2 |
| Auto Bodyguard Spray On Paint Protection | | |
| MANUFACTURER'S NAME | EMERGENCY TELEPHONE NUMBER | |
| Auto Bodyguard, Inc | CHEM TEL (800) 255 3924 | |
| ADDRESS | TELEPHONE NUMBER FOR PRODUCT INFORMATION | |
| 5100 N O Connor Blvd, Suite 100 | (214) 393-2200 | |
| CITY, STATE, ZIP | DATE PREPARED: June 7, 2015 | |
| Irving, Texas 75039-5594 | SUPERCEDES: | |

SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

| HAZARDOUS COMPONENTS | CAS # | % | OSHA PEL | | ACGIH TWA | | SARA | RQ |
|--|-------------|------------|-----------------|-------|-----------|-------|-----------|-----|
| | | | PPM | MG/M3 | PPM | MG/M3 | TITLE III | LBS |
| Poly(oxy-1,2-ethanediyl), alpha-(2-propylheptyl)-omega-hydroxy | 160875-66-1 | not listed | not established | | | | | |
| Water | 7732-18-5 | not listed | | | | | | |
| | | | | | | | | |
| | | | | | | | | |

SECTION 3 - HEALTH HAZARD DATA

| ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE | EMERGENCY AND FIRST AID PROCEDURES |
|---|---|
| INHALATION: High vapor/aerosol concentrations (attainable at elevated temperatures well above ambient) are irritating to the eyes and the respiratory tract, and may cause headaches, dizziness or other central nervous system effects. | Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for medical attention. |
| SKIN: Low order of toxicity. Skin contact may aggravate an existing dermatitis condition. | Flush with large amounts of water; use soap if available. Remove grossly contaminated clothing, including shoes, and launder before reuse. Do not apply ointments. |
| EYES: Slightly irritating, but does not injure eye tissue. | Flush with large amounts of cool water at low pressure for at least 15 minutes. |
| INGESTION: Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury. Minimal toxicity. | If swallowed, DO NOT induce vomiting. Keep at rest. If conscious, immediately drink two glasses of water. Get prompt medical attention. |
| <div> <div>CARCINOGENICITY</div> <div>NTP?</div> <div>OSHA REGULATED?</div> </div> | |
| The NTP, IARC, or OSHA does not consider this product or its components carcinogenic. | |

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Data not available

SECTION 4 - FIRE FIGHTING MEASURES

| | | |
|--|-------------|---------------------|
| FLASH POINT | NFPA RATING | FLAMMABILITY LIMITS |
| >100 degrees C | | LEL: n/a UEL: 4.9 |
| EXTINGUISHING MEDIA: | | |
| Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. | | |
| SPECIAL FIREFIGHTING PROCEDURES: | | |
| Use foam, dry chemical or water spray to extinguish fire. Self contained positive pressure breathing apparatus and protective clothing should be worn in fighting fires involving chemicals. | | |
| UNUSUAL FIRE AND EXPLOSION HAZARDS: | | |
| None known | | |

SECTION 5 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Eliminate ignition sources in spilled area. Care should be taken when entering spilled area, as surfaces can be very slippery. Dam, divert and absorb residual material and transfer into container for disposal. Should use Class D container for landfill. Avoid storm or sanitary sewers or any natural waterway.

SECTION 6 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep containers closed when not in use and store in cool, dry and well ventilated area. Do not expose container or contents to potential ignition sources. Containers of this material may be hazardous when emptied and may contain residue vapor, liquid, and/or solids.

SECTION 7 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION: None normally required

VENTILATION

Recommended

SPECIAL: Maintain minimum TWA and STEL levels

OTHER: Engineering and work controls as required

PROTECTIVE GLOVES:

EYE PROTECTION:

Nitrile rubber gloves or Viton for extended exposure or sensitive skin.

Safety goggles recommended

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required under normal use.

WORK/HYGENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

SECTION 8 - PHYSICAL / CHEMICAL PROPERTIES

BOILING POINT

>190 degrees F

SPECIFIC GRAVITY (WATER = 1)

1

VAPOR PRESSURE

Not available for product

pH

7

VAPOR DENSITY (AIR = 1)

(air-1) heavier

EVAPORATION RATE:

(water=1) >0.01

SOLUBILITY IN WATER

Dispersible

% VOLATILE (BY WEIGHT)

(including water) 100%

APPEARANCE AND ODOR

Orange liquid

VOLATILE ORGANIC COMPOUNDS (VOC's)

0% wt./wt.

STATE COMPLIANCE: CA ARB VOC Compliant

SECTION 9 - STABILITY AND REACTIVITY

STABILITY

UNSTABLE:

STABLE: XXXX

CONDITIONS TO AVOID:

Keep away from extreme heat and ignition sources.

INCOMPATIBILITY (MATERIALS TO AVOID):

none

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: None known

HAZARDOUS POLYMERIZATION

MAY OCCUR

WILL NOT OCCUR: XXXX

SECTION 10 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose in accordance with Local, State, and Federal Regulations. This product may produce hazardous vapors or fumes in a disposal container creating a dangerous environment. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals. Do not flush to sanitary sewer or waterway.

The information contained herein is believed to be accurate but not warranted to be so. Data and calculations are furnished by the manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable, and suited to the circumstances of use. Tri-Pro Group, Inc. assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.